

 1PXL COVE LIGHT XR



Designer: ABC Consulting  
Glitter Glutch - Las Vegas, USA



Designer: Wagenknecht Architekten  
HafenCity - Hamburg, Germany

## 1PXL COVE LIGHT XR

### RGB

1PXL Cove Light XR RGB (12 SMD)

**MB.CL.5010100**

### Cold White

1PXL Cove Light XR CW (12 SMD)

**MB.CL.5060100**

1PXL Cove Light XR CW DLX (24 SMD)

**MB.CL.5062100**

### Warm White

1PXL Cove Light XR WW (12 SMD)

**MB.CL.5070100**

1PXL Cove Light XR WW DLX (24 SMD)

**MB.CL.5072100**

### Dynamic White™

1PXL Cove Light XR DW (24 SMD)

**MB.CL.5080100**

#



Cove Light XR combines compact design with advanced LED technology to accentuate alcoves and recessed spaces, with sophisticated multicolored and white light. Cove Light XR features a generous 180° locking rotation for flexible mounting and installation scenarios. A wide beam angle of 120° ensures an even glow of light. Twelve high-performance surface-mounted LEDs provide an intense light output turning 1PXL Cove Light XR into the perfect solution for any architectural landscape or decorative hospitality environment, as well as recreational and commercial surroundings, boutiques or retail fashion stores.

Doubling the light output, Traxon's 1PXL Cove Light CW/DW DLX offer 24 high performance SMD LEDs, ideally suited for applications requiring an ultra bright light output in Cold White, Warm White and Dynamic White™.

#### TECHNICAL SPECIFICATION OPTIONS

FEATURES	Slim profile cove light; 180° free-locking rotation; Smart Chip™; Auto-addressing; TX Connect™ Smart; Plug 'n' Play solution (simple on/off installations possible without additional controller for White Line)	
BEAM ANGLE		
COLOR	   	RGB Cold White Warm White Dynamic White™
ENVIRONMENT	    	INDOOR IP65 IP66 IP67 IP68
CONTROL	DMX	
WEIGHT	0.2kg / 0.44lb	
DIMENSIONS	(L x W x H) 295mm x 35mm x 44.7mm, 11.61" x 1.38" x 1.76"	

